

Cat.5e SF-UTP Cable

Jacket: PVC, LSZH (Low Smoke Zero Halogen), Outdoor PE

Packaging: 305MReel Box/ Reel in Box

Part No	TP-SFUTP-C5e
No. of Pairs	4
Cable Type	SF-UTP
Conductor Size	24AWG
Core Dimension(mm)	1.03
Overall Dimension(mm)	6.42
NVP(%)	66

Standard Compliances

- ISO/IEC 11801:2011(Ed.2.2)
- IEC 61156-5:2009(Ed.2.0)
- EN 50173-1:2011
- EN 50173-2:2007 including amendment A1:2010
- ANSI/TIA-568-C.2:2009

Features and Benefits

- Positive PSACR beyond 155MHz for future bandwidth requirements
- Characterized and tested to 100 MHz
- Unique product-specific packaging for ease of identification
- Every master reel is tested to ensure electrical performance compliance
- Print legend contains footage marking from 305M to 0M or 500M to 0M
- RoHS compliant
- ETL / EC Verified

Applications

- IEEE 802.3: 1000BASE-T (Gigabit Ethernet), 100BASE-TX, 10BASE-T
- 52/155 Mp/s ATM
- ANSI X3.263: 100 Mb/s
- 4/16 Mb/s Token Ring

