
Removable outdoor optical cable

GYWTA






Application:

- Pieces of long-distance aerial and pipe laying!!!
- Pieces of rural optical fiber to the home some distance to extract (tao fiber)
- Spectral line! Mixer city monitory point to point light extraction (tao fiber), save molten fiber occasions

Product description:

Outside the removable (Tao fiber) cable - GYWTA models use miniature pine casing, is 250 um fiber set into the pine casing of high modulus materials, loose tube filling waterproofing compound tube, a case of a core fiber model, to join the water-blocking material, carries on the SZ to wring, ensure you long, fiber optic cable is applied to longitudinally wrap a layer of moisture proof aluminum belt, easy to extract Tao fiber, a layer of sheathed extrusion molding



Technical Parameters

Cable Code	Fiber Count	Cable Size (mm)	Cable Weight (kg/km)	Tensile (N)		Crush (N/100mm)		Crush Resistance (mm)		Range of Temperature
				Long Term	Short Term	Long Term	Short Term	Dynamic	Static	(,C)
TP-GYWTA-06	6	8.0	65	600	1500	300	1000	20 D	10D	—40∼+70
TP-GYWTA-08	8	8. 0	70	600	1500	300	1000	20 D	10D	
TP-GYWTA-12	12	8.0	75	600	1500	300	1000	20 D	10D	
TP-GYWTA-24	24	9.5	90	600	1500	300	1000	20D	10D	
Fiber Type		G652D	50/125	62.5/125	G657A1	G657A2	OM3-150	OM3-300	OM4	
Jacket Material		PE		LSZH						

Characteristics:

- Good mechanical and temperature performance
- Crush resistance and flexibility
- Sm all dianeter ,lighe weighet and friendly installation
- Long delivery length