

Multi-pair Cable Indoor

Multi-pair cable - 10 pair - Indoor 24AWG


Conductor	Solid Annealed Copper
Insulation	Solid Insulation,HDPE Material
Paired	2 Wires Twist
Compose Of Cable Core	Every Elementary Unit Bundle With Double Color Tape
Cable Core Bundle Method	Polyester Tape
Moistureproof Tape	NO
Jacket	Black Color PVC
Packing Request	Iron Spool,Rolls or Wooden Spool,

Core Structure and Jacket Thickness

Diameter	Pairs	Cable Structure		Jacket thick	Outer Diameter
		First Layer	Second Layer		
0.5mm	10	1*10		0.9+/-0.1	7.5+/-0.2

Insulation Chromato Gram

Serial NO.	Insulation Chromato Gram	Serial NO.	Insulation Chromato Gram
1	White/Blue	14	Black/Brown
2	White/Orange	15	Black/Gray
3	White/Green	16	Yellow/Blue
4	White/Brown	17	Yellow/Orange
5	White/Gray	18	Yellow/Green
6	Red/Blue	19	Yellow/Brown
7	Red/Orange	20	Yellow/Gray
8	Red/Green	21	Violet/Blue
9	Red/Brown	22	Violet/Orange
10	Red/Gray	23	Violet/Green
11	Black/Blue	24	Violet/Brown
12	Black/Orange	25	Violet/Gray
13	Black/Green		



Electronic Requirement

ITEM		REQUIRMENT
		0.50 mm
Single Wire DC (Maximum)	ohm/Km	90.5
DC Resistance Unbalance	Maximum %	2.2
Equivalent Capacitance (Working Capacitance):(800Hz/km) nF/km	Maximum	10Pair =53.6
Capacity Unbalance Between Pairs (800Hz/300m) pF/km		87
Electrical Strength,DC		
Action Time		1 min
Between Conductor and Conductor		1 KV

